

3TF50 World Series Power Contactor

Application

The contactor is a straight motion mechanism having double-breaking contacts. The auxiliary contacts are arranged 2NO.2NC at most, it is employed the flexible locking connection between the contact support and core , three are no arcisolated panle in the le ? 22A contactors, in the le ? 32A contactors, there are moulded are-chute with arc-isolated panel. Because all contacts are made of high nonfusibility and against corrosion silver alloy. All series products can be mounted by screws, le ? 32A contactor also by installation rail .

Model	Part Number	Amp	HP@230V	HP@460V	HP@575V	Weight Lbs
3TB-40	3TB40	9	3	5	7.5	0.20
3TB-41	3TB41	12	3	7.5	10	0.20
3TB-42	3TB42	16	3	10	10	0.20
3TB-43	3TB43	22	7.5	15	20	0.20
3TB-44	3TB44	32	10	25	30	0.20
3TF-40	3TF4022	9	3	5	7.5	0.20
3TF-41	3TF4122	12	3	7.5	10	0.20
3TF-42	3TF4222	16	5	10	10	0.22
3TF-43	3TF4322	22	7.5	15	20	0.22
3TF-44	3TF4422	32	10	25	30	0.36
3TF-45	3TF4522	38	15	28	30	0.36
3TF-46	3TF4622	45	20	40	50	0.73
3TF-47	3TF4722	63	25	50	60	0.73
3TF-48	3TF4822	75	30	60	75	1.14
3TF-49	3TF4922	85	40	75	100	1.14
3TF-50	3TF5022	110	50	100	125	1.59
3TF-51	3TF5122	140	60	110	150	1.59
3TF-52	3TF5222	170	60	125	150	2.27
3TF-53	3TF5322	205	75	150	200	2.27
3TF-54	3TF5422	250	100	200	250	2.91
3TF-55	3TF5522	300	125	250	300	2.91
3TF-56	3TF5622	400	150	300	400	3.95
3TF-57	3TF5722	475	200	400	500	3.95
3TF World Series in IEC standard	Rated operating Current AC-380V	Rated voltage	Standard power ratings of 3-phase			
			220/230V	380/400V	480V/500V	690/660V
	(A)	(V)	KW	KW	KW	KW
3TB40	9	690	2.4	4	5.5	5.5
3TB41	12	690	3.3	5.5	7.5	7.5
3TB42	16	690	4	7.5	10	11
3TB43	22	690	6.1	11	11	11

3TB44	32	690	8.5	15	21	23	
3TF40	9	690	2.4	4	5.5	5.5	
3TF41	12	690	3.3	5.5	7.5	7.5	
3TF42	16	690	4	7.5	10	11	
3TF43	22	690	6.1	11	11	11	
3TF44	32	690	8.5	15	21	23	
3TF45	38	690	11	18.5	25	23	
3TF46	45	690	15	22	30	39	
3TF47	63	690	18.5	30	41	55	
3TF48	75	690	22	37	50	67	
3TF49	85	690	26	45	39	67	
3TF50	110	690	37	55	76	100	
3TF51	140	690	43	75	98	100	
3TF52	170	690	55	90	118	156	
3TF53	205	690	64	110	145	156	
3TF54	250	690	78	132	178	235	
3TF55	300	690	93	160	210	235	
3TF56	400	690	125	200	284	375	
3TF57	475	690	145	250	329	375	
3TF3-0X-- 3TF4-0X--- 3TF5-0X--	50HZ			60HZ		50/60HZ	
	24V	B0	24V	C1	24V	C2	
	48V	H0	110V	G1	42V	D2	
	110V	F0	120V	K1	110V	G2	
	220V	M0	208V	M1	120V	K2	
	230V	P0	220V	N1	208V	M2	
	240V	U0	230V	L1	220V	N2	
	380V	Q0	240V	P1	240V	P2	
	415V	R0	440V	R1	440V	R2	
	500V	S0	575V	S1	575V	S2	



Product link : <https://www.nofuelpower.com/?p=1711>